

Data sheet for three-phase Squirrel-Cage-Motors Innomotics



Motor type : 1CV3204A

INNOMOTICS SD - 200 L - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			cosφ ³⁾			I _A /I _N I _V /I _N	M _A /M _N T _I /T _N	M _K /M _N T _B /T _N	IE-CL
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	30.00	-/-	53.00	2955	97.0	93.3	93.5	92.9	0.87	0.84	0.76	7.0	2.5	3.3	IE3
690	Y	50	30.00	-/-	31.00	2955	97.0	93.3	93.5	92.9	0.87	0.84	0.76	7.0	2.5	3.3	IE3
460	Δ	60	33.50	-/-	52.00	3555	90.0	93.0	92.8	91.4	0.87	0.84	0.77	7.1	2.5	3.3	IE3
460	Δ	60	30.00	-/-	47.00	3560	80.0	92.4	91.9	90.1	0.87	0.84	0.77	8.5	3.0	3.7	IE3
IM B3 / IM 1001		FS 200 L		IP55		UKCA		IEC/EN 60034			IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 32.20 s 52.70 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	67.0 / 80.0 dB(A) 2) 3)	77.0 / 84.0 dB(A) 2) 3)	Vibration severity grade	A
Moment of inertia	0.1340 kg m²		Thermal class	F
Bearing DE NDE	6212 2Z C3	6212 2Z C3	Duty type	S1
Bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	220 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled
			Carbon footprint (without options)	855kg

Terminal box

Terminal box position	top	Main cable entry	2xM50x1.5
Material of terminal box	cast iron	Main cable gland	2 plugs
Type of terminal box	TB1 L01	Auxiliary cable entry	1xM20x1.5
Contact screw thread	6xM6	Auxiliary cable gland	1 plug
Max. cross-sectional area	25.0 mm ²		

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque
1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LV	Technical reference	Created by IPC	Approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
INNOMOTICS	Document type Technical data sheet			Document status Released			
	Document title 1LE1503-2AA43-4AB4-Z H01			Document number TDS-260512-135251			
Restricted © Innomotics 2026				Revision AA	Creation date 2026-05-12	Language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors Innomotics



Motor type : 1CV3204A

INNOMOTICS SD - 200 L - IM B3 - 2p

Special design

H01 Bolted on mounting feet (instead of cast)

I_{Δ}/I_N = locked rotor current / current nominal
 M_{Δ}/M_N = locked rotor torque / torque nominal
 M_b/M_N = break down torque / nominal torque

1) $L_{100\%}$ according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411


Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LV	Technical reference	Created by IPC	Approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents		
INNOMOTICS	Document type Technical data sheet			Document status Released			
	Document title 1LE1503-2AA43-4AB4-Z H01			Document number TDS-260512-135251			
Restricted © Innomotics 2026				Revision AA	Creation date 2026-05-12	Language en	Page 2/2

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment or damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Weitergabe sowie Vervielfältigung, Verbreitung und/oder Bearbeitung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung, Gebrauchsmuster- oder Geschmacksmusterertragung vorbehalten.

Confie à titre de secret d'entreprise. Tous droits réservés. Communiqué como secreto empresarial. Reservados todos os direitos. Довіреність в якості секрету підприємства. Всі права захищені. Confiado como secreto de empresa. Nos reservamos todos los derechos.



Technische Änderungen vorbehalten!
Technical data are subject to change!

Tolerance	Surface	Material	Weight	Scale mm
1LE1503-2AA43-4AB4-Z H01	Author	Dimensional drawing Maßzeichnung		
	Creator12/05/2026 IPC			
	Approval Created automatically			
	Department IN LVM			
INNOMOTICS	Change Order	MLFB	Doc Type /	
	Doc State Released	Item No	Paper Size A3	
	Revision AA Index RS	Doc No	1st Language en 2nd Language de	
	Project No	Ref No	Sheet 1 of 1	

© Innomotics 2026

Restricted