



Customer information packet

L3504-50

.5/.37KW, 1425RPM, 1PH, 50HZ, 56, 3424LC, TEFC

ABB Ltd Drives

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	56
Frame Material	Steel
Frequency	50.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Cap Run
Output @ Frequency	.370 KW @ 50 HZ
Phase	1
Synchronous Speed @ Frequency	1500 RPM @ 50 HZ
Voltage @ Frequency	110.0 V @ 50 HZ 220.0 V @ 50 HZ
Agency Approvals	C UR US CE CURUS UKCA WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	5.000 A @ 110.0 V 2.500 A @ 220.0 V
Design Code	-
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	72.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None

Part detail

Revision	F
Type	AC
Mech. spec.	34G375
Base	
Status	PRD/A
Elec. spec.	34WGR778
Layout	34LYG375
Eff. date	03-07-2025
CD Diagram	CD0055
Poles	04
Leads	6#18
Proprietary	False
Created date	10-10-2023

Heater Indicator	No Heater
High Voltage Full Load Amps	2.5 a
Insulation Class	B
Inverter Code	Not Inverter
KVA Code	J
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3424LC
Mounting Arrangement	F1
Number of Poles	4
Overall Length	11.97 IN
Power Factor	93
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.25
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1425 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1372L									
CAT.NO.	L3504-50								
SPEC.	34G375R778								
HP	.5/.37KW								
VOLTS	110/220								
AMP	5/2.5								
R.P.M. (1/MIN)	1425								
FRAME	56		HZ	50			PH	1	
SER.F.	1.25	CODE	J	DES	-	CL	B		
NEMA-NOM-EFF	72.7	PF	93						
RATING	40C AMB-S1 CONT								
CC			IP44 IC411 19KG						
DE	6203		ODE	6203					
ENCL	TEFC	SN							
	IE2-50HZ 68(75%),60 (50%)								

Parts list

Part number	Description	Quantity
SA418779	SA 34G375R778	1.000 ea
RA410685	RA 34G375R778	1.000 ea
OC3040F18SP	7YL OIL CAP 40MFD/370V	1.000 ea
EC1270A02SP	ELEC CAP, 270-324 MFD, 125V, 1.48D X 3.	1.000 ea
NS2512A01	INSULATOR, CONDUIT BOX X	1.000 ea
34CB3002A	CB CAST W/.88 DIA HOLE	1.000 ea
34GS1029A01	GASKET, CONDUIT BOX	1.000 ea
51XB1016A07	10-16 X 7/16 HXWSSLD SERTYB	2.000 ea
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	3.000 ea
34EP3102A01SP	FR ENDPLATE, MACH	1.000 ea
34CB3801	CAPACITOR BOX, DIE CAST	1.000 ea
34GS3002	GASKET, CAPACITOR BOX	1.000 ea
51XB1214A08	12-14 X 1/2HX WS SL SR TYBX	2.000 ea
HW5100A03	WAVY WASHER (W1543-017)	1.000 ea
34EP3102A02SP	FR/PU ENDPLATE, MACH	1.000 ea
XY1032A02	10-32 HEX NUT DIRECTIONAL SERRATION	4.000 ea
34FN3002A01SP	EXTERNAL FAN, PLASTIC, .637/.639 HUB W/	1.000 ea
34FH4002A01SP	IEC FH NO GREASER PRIMED	1.000 ea
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 ea
34CB4517	CB LID 4 MTG HOLES .22 DIA STAMPED, FOR	1.000 ea
34GS1031A01	GASKET, FLAT CONDUIT BOX LID (LEXIDE)	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	4.000 ea
HA7000A04	KEY RETAINER 0.625 DIA SHAFTS	1.000 ea
34GS5003A01	FOAM SLEEVE, ID = 2 1/16" X 4 3/8"	3.000 ea
MG1050G01	CELEROL MEDIUM CHARCOAL METALLIC GRAY	0.014 ga
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
SP5051B57	MODEL 34 TYPE LC STATIONARY SWITCH	1.000 ea
HA3100A44	THRUBOLT 10-32 X 8.000	4.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/22	1.000 ea
LB1624	COMBINED WARNING LABEL, ISO/ANSI PICTOGR	1.000 ea

LC0001	CONN LABEL TYPE L, 6 LEAD, DUAL VOLTS, R	1.000 ea
NP1372L	ALUM UL CE UKCA WEEE CC, A60	1.000 ea
35PA1005	PKG GRP, BLANK PK1012	1.000 ea
HW2501D13	KEY, 3/16 SQ X 1.375	1.000 ea

Accessories

Part number	Description	Multiplier
34-171	C FACE KIT	A8

AC Induction Motor Performance Data

Record # 101512

Typical performance - not guaranteed values

Winding: 34WGR778-R002			Type: 3424LC		Enclosure: TEFC			
Nameplate Data			220 V, 50 Hz: High Voltage Connection					
Rated Output (KW)		.37	Full Load Torque		1.811 LB-FT			
Volts		110/220	Start Configuration		direct on line			
Full Load Amps		5/2.5	Breakdown Torque		4.92 LB-FT			
R.P.M.		1425	Pull-up Torque		4.25 LB-FT			
Hz	50	Phase	1	Locked-rotor Torque		5.35 LB-FT		
NEMA Design Code		-	KVA Code	J	Starting Current		18.6 A	
Service Factor (S.F.)		1.25	No-load Current		1.33 A			
NEMA Nom. Eff.		72.7	Power Factor		93	Line-line Res. @ 25°C		4.8692 Ω A Ph 4.0443 Ω B Ph
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		53°C	
S.F. Amps		6/3	Temp. Rise @ S.F. Load		63°C			

Load Characteristics 220 V, 50 Hz, 0.37 KW

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	66	79	86	90	92	93	92
Efficiency	44	61.6	69.4	72.8	73.8	73.1	73.8
Speed	1484.9	1473.4	1460.5	1446.1	1429	1408.9	1429
Line amperes	1.47	1.74	2.14	2.58	3.1	3.69	3.1

ABB Motors and Mechanical Inc.

WINDING # 34WGR778

Typical performance - not guaranteed values.

0.37 KW 1 PH 50 HZ 1425 RPM 220 V 3424LC

TORQUES (LB-FT): PO=4.92 PU=4.25 LR=5.35 LRA=18.6





