

ODE-3-120070-301A

Optidrive E3 VFD Datasheet

1.5 kW (2 HP), 7 A, 200-240 V, 3PH

**IP66 Outdoor Non-switched Variable
Frequency Drive**



Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	9.5 A
Supply Fuse or MCB (Type B)	16 A

Output Ratings

Motor Output Rating	1.5 kW (2 HP)
Output Voltage	0 – Supply Voltage
Output Current	7 A

Cable Information

Max Supply Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	No Internal EMC Filter
Brake Transistor	No Internal Brake Transistor
Enclosure	IP66 Outdoor Non-switched
Display	LED
PCB Coating	-

Dimensions

Size	1
Height	232 mm (9.13 in)
Width	161 mm (6.34 in)
Depth	152 mm (5.98 in)
Weight	2.3 kg (5.07 lbs)
Fixings	4 x M4

Packaged Dimensions

Height	205 mm (8.07 in)
Width	210 mm (8.27 in)
Depth	345 mm (13.58 in)
Weight	2.9 kg (6.39 lbs)



How we measure our drives and packaging



Drive Dimensions



Packaging Dimensions