

ODE-3-220105-1F4A-01

Optidrive E3 Single Phase VFD Datasheet

1.1 kW (1.5 HP), 10.5 A, 200-240 V, 1PH

IP66 Outdoor Non-switched Variable
Frequency Drive with EMC Filter



Input Ratings

Supply Voltage	200-240 V
Input Phases	1
Supply Current Continuous	14 A
Supply Fuse or MCB (Type B)	20 A

Output Ratings

Motor Output Rating	1.1 kW (1.5 HP)
Output Voltage	0 – Supply Voltage
Output Current	10.5 A

Cable Information

Max Supply Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Internal EMC Filter
Brake Transistor	Internal Braking Transistor
Enclosure	IP66 Outdoor Non-switched
Display	LED
PCB Coating	-

Dimensions

Size	2
Height	257 mm (10.12 in)
Width	188 mm (7.4 in)
Depth	172 mm (6.77 in)
Weight	3.5 kg (7.72 lbs)
Fixings	4 x M4

Packaged Dimensions

Height	215 mm (8.46 in)
Width	235 mm (9.25 in)
Depth	375 mm (14.76 in)
Weight	4.2 kg (9.26 lbs)



How we measure our drives and packaging



Drive Dimensions



Packaging Dimensions