

ODV-3-220070-1F1A-MN

Optidrive Eco VFD Datasheet

1.5 kW (2 HP), 7 A, 200-240 V, 1-3PH

IP66 Non Switched Outdoor Variable
Frequency Drive with EMC Filter and TFT
Display



Input Ratings

Supply Voltage	200-240 V
Input Phases	1
Supply Current Continuous	15.2 A
Supply Fuse or MCB (Type B)	25 A

Output Ratings

Motor Output Rating	1.5 kW (2 HP)
Output Voltage	0 – Supply Voltage
Output Current	7 A

Cable Information

Max Supply Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	No Brake Transistor
Enclosure	IP66 Non Switched Outdoor
Display	TFT Display
PCB Coating	Standard

Dimensions


Size	2
Height	257 mm (10.12 in)
Width	188 mm (7.4 in)
Depth	172 mm (6.77 in)
Weight	3.5 kg (7.72 lbs)
Fixings	4 x M4

Packaged Dimensions


Height	215 mm (8.46 in)
Width	235 mm (9.25 in)
Depth	375 mm (14.76 in)
Weight	4.2 kg (9.26 lbs)



How we measure our drives and packaging



Drive Dimensions



Packaging Dimensions