


Technical Data Sheet
Electric Motor 1 phase in Aluminum IE1



L (standard motor)

426

L (motor w/brake)

NA

L (motor w/forced ventilation)

546

L (motor without ventilation)

370

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
-	-	-	-	-	28j6	60	8	24	31	M10x22	-	-	220	187	130	110	160	M8	3.5

Electrical Data

Type	UCC 112M-4	
Poles	4/1500	Poles
Power	3.70	Kw
Voltage	230	V
Frequency	50	Hz
Speed	1400	rpm
Nominal current	21.40	A
Power factor	0.98	
Efficiency 100%	83.1	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	27.28	N.m
Ta/Tn	2.5	
Ia/In	5.7	
Tm/Tn	1.8	

Mechanical Data

Shaft height	-
Construction form	B14
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	- dB(A)
Weight	35 kg
Bearing DE	6306 2Z C3
Bearing NDE	6206 2Z C3

Extra Data

Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	80	W
Three-phase forced ventilation	Power	NA	W