


Technical Data Sheet

Electric Motor Three phase in Aluminum IE3



L (standard motor)

384

L (motor w/brake)

460

L (motor w/forced ventilation)

495

L (motor without ventilation)

339

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
100	160	140	63	12	28j6	60	8	24	31	M10x22	198	176	205	252	215	180	250	15	4

Electrical Data

Type	PE31/UM3A*	
	100L1-4	
Poles	4/1500	Poles
Power	2.20	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1445	rpm
Nominal current	4.70	A
Power factor	0.78	
Efficiency 100%	86.7	%
Efficiency 75%	86.1	%
Efficiency 50%	83.7	%
Torque	14.5	N.m
Ta/Tn	2.3	
Ia/In	7.5	
Tm/Tn	2.3	

Mechanical Data

Shaft height	100
Construction form	B35
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	70 dB(A)
Weight	27 kg
Bearing DE	6206 2Z C3
Bearing NDE	6206 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-12	Brake torque	32	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	65	W
Three-phase forced ventilation	Power	65	W