


Technical Data Sheet
Electric Motor Three phase in Aluminum IE3



L (standard motor)

390

L (motor w/brake)

490

L (motor w/forced ventilation)

505

L (motor without ventilation)

340

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
-	-	-	-	-	28j6	60	8	24	31	M10x22	-	-	230	178	215	180	250	15	4

Electrical Data

Type	PE31/UM3A*	
	112M-2	
Poles	2/3000	Poles
Power	4.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	2925	rpm
Nominal current	7.45	A
Power factor	0.88	
Efficiency 100%	88.1	%
Efficiency 75%	88.4	%
Efficiency 50%	86.7	%
Torque	13.06	N.m
Ta/Tn	2.3	
Ia/In	8.3	
Tm/Tn	2.3	

Mechanical Data

Shaft height	-
Construction form	B5
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	83 dB(A)
Weight	34 kg
Bearing DE	6306 2Z C3
Bearing NDE	6306 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-14	Brake torque	60	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	80	W
Three-phase forced ventilation	Power	80	W