


Technical Data Sheet
Electric Motor Three phase in Aluminum IE3



L (standard motor)

503

L (motor w/brake)

590

L (motor w/forced ventilation)

630

L (motor without ventilation)

391

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
-	-	-	-	-	38k6	80	10	33	41	M12x28	-	-	265	198	265	230	300	15	4

Electrical Data

Type	PE31/UM3A*	
	132M-4	
Poles	4/1500	Poles
Power	7.50	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1465	rpm
Nominal current	14.42	A
Power factor	0.83	
Efficiency 100%	90.4	%
Efficiency 75%	90.1	%
Efficiency 50%	88.8	%
Torque	48.89	N.m
Ta/Tn	2	
Ia/In	7.4	
Tm/Tn	2.3	

Mechanical Data

Shaft height	-	
Construction form	B5	
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S1	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	75	dB(A)
Weight	63	kg
Bearing DE	6308 2Z C3	
Bearing NDE	6308 2Z C3	

Extra Data

Applicable brakes

DC brake	REB-05-16	Brake torque	80	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	55	W
Three-phase forced ventilation	Power	55	W