


Technical Data Sheet
Electric Motor Three phase in Aluminum IE3



L (standard motor)

477

L (motor w/brake)

570

L (motor w/forced ventilation)

605

L (motor without ventilation)

371

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
132	216	178	89	12	38k6	80	10	33	41	M12x28	254	214	265	324	265	230	300	15	4

Electrical Data

Type	PE31/UM3A*	
	132M1-6	
Poles	6/1000	Poles
Power	4.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	965	rpm
Nominal current	8.99	A
Power factor	0.74	
Efficiency 100%	86.8	%
Efficiency 75%	86.9	%
Efficiency 50%	85.9	%
Torque	39.58	N.m
Ta/Tn	2	
Ia/In	6.8	
Tm/Tn	2.1	

Mechanical Data

Shaft height	132	
Construction form	B35	
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S1	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	73	dB(A)
Weight	52	kg
Bearing DE	6308 2Z C3	
Bearing NDE	6308 2Z C3	

Extra Data

Applicable brakes

DC brake	REB-05-16	Brake torque	80	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	55	W
Three-phase forced ventilation	Power	55	W