


Technical Data Sheet
Electric Motor Three phase in Aluminum IE3



L (standard motor)

610

L (motor w/brake)

NA

L (motor w/forced ventilation)

730

L (motor without ventilation)

552

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
-	-	-	-	-	42k6	110	12	37	45	M16x36	-	-	326	235	215	180	250	M12	4

Electrical Data

Type	PE31/UM3A*	
	160M-4	
Poles	4/1500	Poles
Power	11.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1475	rpm
Nominal current	20.68	A
Power factor	0.84	
Efficiency 100%	91.4	%
Efficiency 75%	91.8	%
Efficiency 50%	90.7	%
Torque	71.22	N.m
Ta/Tn	2.2	
Ia/In	7.5	
Tm/Tn	2.3	

Mechanical Data

Shaft height	-	
Construction form	B14	
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S1	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	77	dB(A)
Weight	98	kg
Bearing DE	6309 2Z C3	
Bearing NDE	6209 2Z C3	

Extra Data

Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	60	W