


Technical Data Sheet
Electric Motor Three phase in Cast Iron IE3



L (standard motor)

445

L (motor w/brake)

550

L (motor w/forced ventilation)

550

L (motor without ventilation)

410

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
-	-	-	-	-	28j6	60	8	24	31	M10x22	-	-	220	193	130	110	160	4xM8	3.5

Electrical Data

Type	PE30/UM3C*	
	112M-6	
Poles	6/1000	Poles
Power	2.20	Kw
Voltage	400	V
Frequency	50	Hz
Speed	935	rpm
Nominal current	5.09	A
Power factor	0.74	
Efficiency 100%	84.3	%
Efficiency 75%	84.7	%
Efficiency 50%	83.0	%
Torque	22.5	N.m
Ta/Tn	2	
Ia/In	6.6	
Tm/Tn	2.1	

Mechanical Data

Shaft height	-
Construction form	B14
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	65 dB(A)
Weight	49 kg
Bearing DE	6306 2Z C3
Bearing NDE	6306 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-14	Brake torque	60	N.m
AC brake	AC6	Brake torque	60	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	80	W
Three-phase forced ventilation	Power	80	W