


Technical Data Sheet
Electric Motor Three phase in Cast Iron IE3



UNIVERSAL
MOTORS



L (standard motor)

745

L (motor w/brake)

855

L (motor w/forced ventilation)

865

L (motor without ventilation)

655

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
160	254	254	108	15	42k6	110	12	37	45	M16x36	320	305	315	420	300	250	350	4x19	5

Electrical Data

Type	PE30/UM3C* 160L-6	
Poles	6/1000	Poles
Power	11.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	970	rpm
Nominal current	22.00	A
Power factor	0.80	
Efficiency 100%	90.3	%
Efficiency 75%	90.9	%
Efficiency 50%	89.6	%
Torque	108.3	N.m
Ta/Tn	2	
Ia/In	7.2	
Tm/Tn	2.1	

Mechanical Data

Shaft height	160
Construction form	B35
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	73 dB(A)
Weight	160 kg
Bearing DE	6309 C3
Bearing NDE	6309 C3

Extra Data

Applicable brakes

DC brake	K8	Brake torque	200	N.m
AC brake	AC8	Brake torque	200	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	60	W