


Technical Data Sheet
Electric Motor Three phase in Cast Iron IE3



L (standard motor)

685

L (motor w/brake)

795

L (motor w/forced ventilation)

805

L (motor without ventilation)

595

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
-	-	-	-	-	42k6	110	12	37	45	M16x36	-	-	315	255	300	250	350	4x19	5

Electrical Data

Type	PE30/UM3C*	
	160M1-8	
Poles	8/750	Poles
Power	4.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	720	rpm
Nominal current	9.30	A
Power factor	0.73	
Efficiency 100%	84.8	%
Efficiency 75%	85.1	%
Efficiency 50%	81.7	%
Torque	53.05	N.m
Ta/Tn	1.9	
Ia/In	6.0	
Tm/Tn	2	

Mechanical Data

Shaft height	-	
Construction form	B5	
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S1	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	68	dB(A)
Weight	120	kg
Bearing DE	6309 C3	
Bearing NDE	6309 C3	

Extra Data

Applicable brakes

DC brake	K8	Brake torque	200	N.m
AC brake	AC8	Brake torque	200	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	60	W