


Technical Data Sheet  
Electric Motor Three phase in Cast Iron IE3



L (standard motor)

685

L (motor w/brake)

NA

L (motor w/forced ventilation)

805

L (motor without ventilation)

595

| Feet |   |   |   |   | Shaft |     |    |    |    |        | Carcass |    |     |     | Flange |     |     |      |   |
|------|---|---|---|---|-------|-----|----|----|----|--------|---------|----|-----|-----|--------|-----|-----|------|---|
| H    | A | B | C | K | D     | E   | F  | G  | GA | X      | AB      | BB | AC  | HD  | M      | N   | P   | S    | T |
| -    | - | - | - | - | 42k6  | 110 | 12 | 37 | 45 | M16x36 | -       | -  | 315 | 255 | 300    | 250 | 350 | 4x19 | 5 |

### Electrical Data

|                 |            |       |
|-----------------|------------|-------|
| Type            | PE30/UM3C* |       |
|                 | 160M2-2    |       |
| Poles           | 2/3000     | Poles |
| Power           | 15.00      | Kw    |
| Voltage         | 400        | V     |
| Frequency       | 50         | Hz    |
| Speed           | 2950       | rpm   |
| Nominal current | 26.50      | A     |
| Power factor    | 0.89       |       |
| Efficiency 100% | 91.9       | %     |
| Efficiency 75%  | 92.3       | %     |
| Efficiency 50%  | 91.2       | %     |
| Torque          | 48.6       | N.m   |
| Ta/Tn           | 2          |       |
| Ia/In           | 8.1        |       |
| Tm/Tn           | 2.3        |       |

### Mechanical Data

|                       |            |       |
|-----------------------|------------|-------|
| Shaft height          | -          |       |
| Construction form     | B5         |       |
| Mechanical protection | 55         |       |
| Heating class         | B          |       |
| Insulation class      | F          |       |
| Service               | S1         |       |
| Ambient temp.         | -10°C-40°C |       |
| Altitude              | 1000       |       |
| Noise                 | 81         | dB(A) |
| Weight                | 136        | kg    |
| Bearing DE            | 6309 C3    |       |
| Bearing NDE           | 6309 C3    |       |

### Extra Data

#### Applicable brakes

|          |    |              |    |     |
|----------|----|--------------|----|-----|
| DC brake | NA | Brake torque | NA | N.m |
| AC brake | NA | Brake torque | NA | N.m |

#### Applicable forced ventilations

|                                 |       |    |   |
|---------------------------------|-------|----|---|
| Single-phase forced ventilation | Power | NA | W |
| Three-phase forced ventilation  | Power | 60 | W |