

Technical Data Sheet
Electric Motor Three phase in Cast Iron IE3



L (standard motor)

810

L (motor w/brake)

965

L (motor w/forced ventilation)

895

L (motor without ventilation)

715

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
180	279	279	121	15	48k6	110	14	42.5	51.5	M16x36	355	350	355	455	-	-	-	-	-

Electrical Data

Type	PE30/UM3C* 180L-8	
Poles	8/750	Poles
Power	11.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	730	rpm
Nominal current	23.90	A
Power factor	0.75	
Efficiency 100%	88.6	%
Efficiency 75%	88.9	%
Efficiency 50%	86.7	%
Torque	143.89	N.m
Ta/Tn	2	
Ia/In	6.5	
Tm/Tn	2	

Mechanical Data

Shaft height	180
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	70 dB(A)
Weight	212 kg
Bearing DE	6311 C3
Bearing NDE	6311 C3

Extra Data

Applicable brakes

DC brake	K8D	Brake torque	400	N.m
AC brake	AC8D	Brake torque	400	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	85	W