

Technical Data Sheet
Electric Motor Three phase in Cast Iron IE3



L (standard motor)

-

L (motor w/brake)

-

L (motor w/forced ventilation)

-

L (motor without ventilation)

-

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T

Electrical Data

Type	PE30/UM3C*	
	225M-2	
Poles	2/3000	Poles
Power	45.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	2970	rpm
Nominal current	76.80	A
Power factor	0.90	
Efficiency 100%	94.0	%
Efficiency 75%	94.1	%
Efficiency 50%	92.7	%
Torque	144.7	N.m
Ta/Tn	2	
Ia/In	7.7	
Tm/Tn	2.3	

Mechanical Data

Shaft height		
Construction form		
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S1	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	86	dB(A)
Weight	359	kg
Bearing DE		
Bearing NDE		

Extra Data

Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	170	W