

Technical Data Sheet
Electric Motor Three phase in Cast Iron IE3



L (standard motor)

950

L (motor w/brake)

NA

L (motor w/forced ventilation)

1070

L (motor without ventilation)

850

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
250	406	349	168	24	65m6	140	18	58	69	M20x42	490	485	485	615	-	-	-	-	-

Electrical Data

Type	PE30/UM3C*	
	250M-4	
Poles	4/1500	Poles
Power	55.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1485	rpm
Nominal current	97.60	A
Power factor	0.86	
Efficiency 100%	94.6	%
Efficiency 75%	94.8	%
Efficiency 50%	93.6	%
Torque	353.7	N.m
Ta/Tn	2	
Ia/In	7.4	
Tm/Tn	2.3	

Mechanical Data

Shaft height	250	
Construction form	B3	
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S1	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	79	dB(A)
Weight	433	kg
Bearing DE	6314 C3	
Bearing NDE	6314 C3	

Extra Data

Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	200	W