


Technical Data Sheet
Electric Motor Three phase in Cast Iron IE3



L (standard motor)

950

L (motor w/brake)

1150

L (motor w/forced ventilation)

1070

L (motor without ventilation)

850

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
-	-	-	-	-	65m6	140	18	58	69	M20x42	-	-	485	370	500	450	550	8x19	5

Electrical Data

Type	PE30/UM3C*	
	250M-6	
Poles	6/1000	Poles
Power	37.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	980	rpm
Nominal current	68.14	A
Power factor	0.84	
Efficiency 100%	93.3	%
Efficiency 75%	93.5	%
Efficiency 50%	92.7	%
Torque	360.5	N.m
Ta/Tn	2	
Ia/In	7.1	
Tm/Tn	2.1	

Mechanical Data

Shaft height	-	
Construction form	B5	
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S1	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	78	dB(A)
Weight	416	kg
Bearing DE	6314 C3	
Bearing NDE	6314 C3	

Extra Data

Applicable brakes

DC brake	K10	Brake torque	500-800	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	200	W