


Technical Data Sheet
Electric Motor Three phase in Cast Iron IE3



L (standard motor)

1060

L (motor w/brake)

1270

L (motor w/forced ventilation)

1215

L (motor without ventilation)

940

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
-	-	-	-	-	75m6	140	20	67.5	79.5	M20x42	-	-	547	410	500	450	550	8x19	5

Electrical Data

Type	PE30/UM3C*	
	280M-6	
Poles	6/1000	Poles
Power	55.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	980	rpm
Nominal current	98.10	A
Power factor	0.86	
Efficiency 100%	94.1	%
Efficiency 75%	94.2	%
Efficiency 50%	93.2	%
Torque	535.9	N.m
Ta/Tn	2	
Ia/In	7.3	
Tm/Tn	2	

Mechanical Data

Shaft height	-	
Construction form	B5	
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S1	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	83	dB(A)
Weight	585	kg
Bearing DE	6317 C3	
Bearing NDE	6317 C3	

Extra Data

Applicable brakes

DC brake	K10D	Brake torque	1000/1500	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	270	W