

Technical Data Sheet
Electric Motor Three phase in Cast Iron IE3



L (standard motor)

1040

L (motor w/brake)

1250

L (motor w/forced ventilation)

1195

L (motor without ventilation)

920

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
280	457	368	190	14	75m6	140	20	67.5	79.5	M20x42	550	485	547	680	500	450	550	8x19	5

Electrical Data

Type	PE30/UM3C* 280S-8	
Poles	8/750	Poles
Power	37.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	740	rpm
Nominal current	73.60	A
Power factor	0.79	
Efficiency 100%	91.8	%
Efficiency 75%	91.9	%
Efficiency 50%	90.9	%
Torque	480.71	N.m
Ta/Tn	1.9	
Ia/In	6.6	
Tm/Tn	2	

Mechanical Data

Shaft height	280
Construction form	B35
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	76 dB(A)
Weight	561 kg
Bearing DE	6317 C3
Bearing NDE	6317 C3

Extra Data

Applicable brakes

DC brake	K10D	Brake torque	1000/1500 N.m
AC brake	NA	Brake torque	NA N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA W
Three-phase forced ventilation	Power	270 W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213