


Technical Data Sheet
Electric Motor Three phase in Cast Iron IE3



L (standard motor)

1335

L (motor w/brake)

1545

L (motor w/forced ventilation)

1515

L (motor without ventilation)

1160

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
-	-	-	-	-	80m6	170	22	71	85	M20x42	-	-	620	530	600	550	660	8x24	6

Electrical Data

Type	PE30/UM3C*	
	315M-8	
Poles	8/750	Poles
Power	75.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	735	rpm
Nominal current	143.60	A
Power factor	0.81	
Efficiency 100%	93.1	%
Efficiency 75%	93.5	%
Efficiency 50%	92.0	%
Torque	974.42	N.m
Ta/Tn	1.8	
Ia/In	6.2	
Tm/Tn	2	

Mechanical Data

Shaft height	-	
Construction form	B5	
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S3-70%	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	82	dB(A)
Weight	1073	kg
Bearing DE	NU 319	
Bearing NDE	6319 C3	

Extra Data

Applicable brakes

DC brake	K11D	Brake torque	2000/2800	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	450	W