


Technical Data Sheet
Electric Motor Three phase in Cast Iron IE4



L (standard motor)

1345

L (motor w/brake)

NA

L (motor w/forced ventilation)

1525

L (motor without ventilation)

1170

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
-	-	-	-	-	80m6	170	22	71	85	M20x42	-	-	620	530	600	550	660	8x24	6

Electrical Data

Type	UM4C 315L1-4	
Poles	4/1500	Poles
Power	160.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1485	rpm
Nominal current	265.64	A
Power factor	0.90	
Efficiency 100%	96.6	%
Efficiency 75%	96.4	%
Efficiency 50%	95.6	%
Torque	1028.9	N.m
Ta/Tn	1.8	
Ia/In	8.5	
Tm/Tn	2.2	

Mechanical Data

Shaft height	-
Construction form	B5
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	88 dB(A)
Weight	1142 kg
Bearing DE	NU 319
Bearing NDE	6319 C3

Extra Data

Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	450	W