


Technical Data Sheet
Electric Motor Three phase in Cast Iron IE4



L (standard motor)

1235

L (motor w/brake)

NA

L (motor w/forced ventilation)

1415

L (motor without ventilation)

1060

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
315	508	406	216	28	80m6	170	22	71	85	M20x42	635	565	620	845	-	-	-	-	-

Electrical Data

Type	UM4C 315S-4	
Poles	4/1500	Poles
Power	110.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1485	rpm
Nominal current	185.25	A
Power factor	0.89	
Efficiency 100%	96.3	%
Efficiency 75%	96.4	%
Efficiency 50%	96.0	%
Torque	707.407407407407 N.m	
Ta/Tn	1.8	
Ia/In	8.5	
Tm/Tn	2.2	

Mechanical Data

Shaft height	315
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	88 dB(A)
Weight	940 kg
Bearing DE	NU 319
Bearing NDE	6319 C3

Extra Data

Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	450	W