


Technical Data Sheet
Electric Motor Three phase in Aluminum IE1



L (standard motor)

390

L (motor w/brake)

490

L (motor w/forced ventilation)

505

L (motor without ventilation)

340

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
112	190	140	70	12	28j6	60	8	24	31	M10x22	220	180	230	286	130	110	160	M8	3.5

Electrical Data

Type	BF31/UMA* 112M-8	
Poles	8/750	Poles
Power	1.50	Kw
Voltage	400	V
Frequency	50	Hz
Speed	710	rpm
Nominal current	4.18	A
Power factor	0.69	
Efficiency 100%	75.0	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	20.17	N.m
Ta/Tn	1.8	
Ia/In	5.0	
Tm/Tn	2	

Mechanical Data

Shaft height	112
Construction form	B34
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	61 dB(A)
Weight	29 kg
Bearing DE	6306 2Z C3
Bearing NDE	6306 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-14	Brake torque	60	N.m
AC brake	AC6	Brake torque	60	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	80	W
Three-phase forced ventilation	Power	80	W