


Technical Data Sheet
Electric Motor Three phase in Aluminum IE1



L (standard motor)

477

L (motor w/brake)

570

L (motor w/forced ventilation)

605

L (motor without ventilation)

371

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
132	216	178	89	12	38k6	80	10	33	41	M12x28	254	214	265	324	165	130	200	M10	3.5

Electrical Data

Type	BF31/UMA* 132M-8	
Poles	8/750	Poles
Power	3.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	710	rpm
Nominal current	7.34	A
Power factor	0.72	
Efficiency 100%	82.0	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	40.35	N.m
Ta/Tn	2	
Ia/In	5.5	
Tm/Tn	2	

Mechanical Data

Shaft height	132
Construction form	B34
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	64 dB(A)
Weight	46 kg
Bearing DE	6308 2Z C3
Bearing NDE	6308 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-16	Brake torque	80	N.m
AC brake	AC7	Brake torque	90	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	55	W
Three-phase forced ventilation	Power	55	W