


Technical Data Sheet

Electric Motor Three phase in Aluminum IE1



L (standard motor)

250

L (motor w/brake)

300

L (motor w/forced ventilation)

360

L (motor without ventilation)

208

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
71	112	90	45	7	14j6	30	5	11	16	M5x12	132	105	147	190	130	110	160	10	3.5

Electrical Data

Type	BF31/UMA* 71M2-4	
Poles	4/1500	Poles
Power	0.37	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1400	rpm
Nominal current	1.07	A
Power factor	0.72	
Efficiency 100%	69.5	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	2.52	N.m
Ta/Tn	2.4	
Ia/In	6.0	
Tm/Tn	2.4	

Mechanical Data

Shaft height	71
Construction form	B35
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	55 dB(A)
Weight	6.2 kg
Bearing DE	6202 2Z C3
Bearing NDE	6202 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-06	Brake torque	4	N.m
AC brake	AC2	Brake torque	10	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	35	W
Three-phase forced ventilation	Power	35	W