


Technical Data Sheet
Electric Motor Three phase in Aluminum IE2



L (standard motor)

636

L (motor w/brake)

NA

L (motor w/forced ventilation)

755

L (motor without ventilation)

577

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
-	-	-	-	-	42k6	110	12	37	45	M16x36	-	-	326	235	300	250	350	15	5

Electrical Data

Type	HE31/UMHA*	
	160L2-2	
Poles	2/3000	Poles
Power	22.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	2890	rpm
Nominal current	38.64	A
Power factor	0.90	
Efficiency 100%	91.3	%
Efficiency 75%	91.7	%
Efficiency 50%	91.0	%
Torque	72.69	N.m
Ta/Tn	4.1	
Ia/In	10.0	
Tm/Tn	3	

Mechanical Data

Shaft height	-	
Construction form	B5	
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S3-70%	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	85	dB(A)
Weight	127	kg
Bearing DE	6309 2Z C3	
Bearing NDE	6209 2Z C3	

Extra Data

Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	60	W