

Technical Data Sheet
Electric Motor Three phase in Aluminum IE2



L (standard motor)

-

L (motor w/brake)

-

L (motor w/forced ventilation)

-

L (motor without ventilation)

-

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T

Electrical Data

Type	HE31/UMHA* 80M3-2	
Poles	2/3000	Poles
Power	1.50	Kw
Voltage	400	V
Frequency	50	Hz
Speed	2820	rpm
Nominal current	3.10	A
Power factor	0.86	
Efficiency 100%	81.3	%
Efficiency 75%	82.6	%
Efficiency 50%	81.5	%
Torque	5.08	N.m
Ta/Tn	3.7	
Ia/In	7.5	
Tm/Tn	3.7	

Mechanical Data

Shaft height		
Construction form		
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S3-70%	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	78	dB(A)
Weight	13.2	kg
Bearing DE		
Bearing NDE		

Extra Data

Applicable brakes

DC brake	REB-05-08	Brake torque	8	N.m
AC brake	AC3	Brake torque	15	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	45	W
Three-phase forced ventilation	Power	45	W