


Technical Data Sheet
Electric Motor 1 phase in Aluminum IE1



L (standard motor)

386

L (motor w/brake)

NA

L (motor w/forced ventilation)

485

L (motor without ventilation)

320

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
-	-	-	-	-	28j6	60	8	24	31	M10x22	-	-	199	167	130	110	160	M8	3.5

Electrical Data

Type	UPC 100L1-4		
Poles	4/1500	Poles	
Power	2.20	Kw	
Voltage	230	V	
Frequency	50	Hz	
Speed	1420	rpm	
Nominal current	13.00	A	
Power factor	0.92		
Efficiency 100%	79.7	%	
Efficiency 75%	-	%	
Efficiency 50%	-	%	
Torque	14.79	N.m	
Ta/Tn	0.3		
Ia/In	4.8		
Tm/Tn	1.7		

Mechanical Data

Shaft height	-
Construction form	B14
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	- dB(A)
Weight	22 kg
Bearing DE	6206 2Z C3
Bearing NDE	6206 2Z C3

Extra Data

Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	65	W
Three-phase forced ventilation	Power	NA	W